

Foxwood Close
Foxwood Industrial Park
Sheepbridge
Chesterfield
Derbyshire
S41 9RB
United Kingdom

T: 01246 261 828 F: 01246 261 830 sales@par.uk.com www.par.uk.com

TECHNICAL DATA

Page 1 of 1

VIDATAPE® SP

**Heavy-Duty Woven Polyester Tape** 

## **DESCRIPTION**

Woven tape constructed from a plain weave of spun PET yarns.

## **APPLICATIONS**

The Vidatape® SP range of heavy-duty woven polyester tapes can be employed as an alternative to cotton sacrifice tapes and used to consolidate and protect coils during manufacture.

It is also employed as bracing and consolidation tape in electric motor & generator stator end windings and exhibits high tensile strength.

Treatment with high temperature resins will enhance the thermal ageing characteristics and permit the usage of Vidatape® SP in Class F (155°C) rated machines.

Vidatape® SP is of particular merit where hand taping is necessary, as it offers little health hazard or skin irritation

0.45mm +0.04mm - 0.03mm
22 N/mm
25
40
130°C (Class B)
155°C (Class F)
180°C (Class H)
None, plain white
Yes
13, 20, 25, 30, 40, 50mm, others on request
$\leq$ 25mm: $\pm$ 1.0mm $>$ 25mm: $\pm$ 1.5mm
25 & 50 metres, others on request
12mm cardboard, others on request

All tests in accordance with IEC 61067-2 unless otherwise stated

## ® Registered trademark

Statements, technical information and recommendations contained herein are based on tests we believe to be reliable but they are not to be construed in any manner as warranties expressed or implied. The user shall determine the suitability of the product for their intended use and the user assumes all risk and liability whatsoever in connection therewith.